



Standard Test Method for Evaluation of Diesel Engine Oils in T-9 Diesel Engine¹

This standard is issued under the fixed designation D 6483; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers an engine test procedure for evaluating diesel engine oils for performance characteristics, including lead corrosion and wear of piston rings and cylinder liners.² This test method is commonly referred to as the Mack T-9.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. See Annex A5 for specific safety precautions.*

1.4 Table of Contents:

Scope	1
Referenced Documents	2
Terminology	3
Summary of Test Method	4
Significance of Use	5
Apparatus	6
General Description	6.1
Test Engine	6.2
Mack T-9 Test Engine	6.2.1
Engine Cooling System	6.2.2
Engine Oil System	6.2.3
Auxiliary Oil System	6.2.4
Blowby Meter	6.2.5
Air Supply and Filtration	6.2.6
Fuel Supply	6.2.7
Intake Manifold Temperature Control	6.2.8
Engine Fluids	7
Test Oil	7.1
Test Fuel	7.2
Engine Coolant	7.3
Cleaning Materials	7.4
Preparation of Apparatus at Rebuild	8
Cleaning of Parts	8.1
Valves, Seats, Guides, and Springs	8.2
Cylinder Liner, Piston, and Piston Ring Assembly	8.3

Injectors and Injection Pump	8.4
Assembly Instructions	8.5
Measurements	8.6
System Time Responses	8.7
Procedure	9
Pretest Procedure	9.1
Engine Start-Up	9.2
Engine Shutdown	9.3
Test Cycle	9.4
Oil Addition/Drain	9.5
Oil Samples	9.6
Oil Consumption Calculations	9.7
Fuel Samples	9.8
Periodic Measurements	9.9
Blowby	9.10
Centrifugal Oil Filter Mass Gain	9.11
Oil Filter ΔP Calculation	9.12
Inspection of Engine, Fuel, and Oil	10
Pre-Test Measurements	10.1
Post-Test Measurements	10.2
Oil Inspection	10.3
Fuel Inspections	10.4
Oil Consumption	10.5
Lab and Engine Test Stand Calibration/Non-Ref Requirements	11
Calibration Frequency	11.1
Calibration Reference Oils	11.2
Test Numbering	11.3
New Laboratories and New Test Stands	11.4
Test Stand and Engine Calibration	11.5
Test Results	11.6
Reference and Non-Reference Oil Test Requirements	11.7
Non-Reference Oil Test Result Severity Adjustments	11.8
Report	12
Reporting Reference Test Results	12.1.1
Deviations from Test Operational Limits	12.1.2
Electronic Transmission of Test Results	12.1.3
Precision and Bias	13
Precision	13.1
Bias	13.2
Keywords	14
Report Forms	Annex A1
Sensor Locations	Annex A2
Procurement of Test Materials	Annex A3
Instructions for Measuring T-9 Cylinder Sleeves	Annex A4
Safety Precautions	Annex A5
Data Dictionary	Annex A6
TBN Measurement Procedure for T-9 Samples	Annex A7
TAN Measurement Procedure for T-9 Samples	Annex A8
Determination of Operational Validity	Annex A9

2. Referenced Documents

2.1 ASTM Standards:³

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.B0 on Automotive Lubricants.

Current edition approved Nov. 1, 2004. Published November 2004. Originally approved in 1999. Last previous edition approved in 2003 as D 6483-03.

² The ASTM Test Monitoring Center will update changes in this test method by means of Information Letters. This edition includes all Information Letters through 03-1. Information Letters may be obtained from ASTM Test Monitoring Center, 6555 Penn Avenue, Pittsburgh, PA 15206-4489, Attention: Administrator.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.



D 86 Test Method for Distillation of Petroleum Products at Atmospheric Pressure

D 93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester

D 97 Test Method for Pour Point of Petroleum Products

D 129 Test Method for Sulfur in Petroleum Products (General Bomb Method)

D 130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test

D 235 Specification for Mineral Spirits (Petroleum Spirits) (Hydrocarbon Dry Cleaning Solvent)

D 287 Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)

D 445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (the Calculation of Dynamic Viscosity)

D 482 Test Method for Ash from Petroleum Products

D 524 Test Method for Ramsbottom Carbon Residue of Petroleum Products

D 613 Test Method for Cetane Number of Diesel Fuel Oil

D 664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration

D 1319 Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption

D 2500 Test Method for Cloud Point of Petroleum Oils

D 2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry

D 2709 Test Method for Water and Sediment in Middle Distillate Fuels by Centrifuge

D 2896 Test Method for Base Number of Petroleum Products by Potentiometric Perchloric Acid Titration

D 4052 Test Method for Density and Relative Density of Liquids by Digital Density Meter

D 4485 Specification for Performance of Engine Oils

D 4737 Test Method for Calculated Cetane Index by Four Variable Equation

D 4739 Test Method for Base Number Determination by Potentiometric Titration

D 5185 Test Method for Determination of Additive Elements, Wear Metals, and Contaminants in Used Lubricating Oils and Determination of Selected Elements in Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)

D 5302 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Deposit Formation and Wear in a Spark-Ignition Internal Combustion Engine Fueled with Gasoline and Operated Under Low-Temperature, Light-Duty Conditions⁴

D 5844 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Rusting (Sequence IID)⁴

D 5967 Test Method for Evaluation of Diesel Engine Oils in T-8 Diesel Engine

E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E 178 Practice for Dealing With Outlying Observations

E 344 Terminology Relating to Thermometry and Hydro-metry

2.2 SAE Standards:⁵

SAE J1995 Engine Power Test Code - Spark Ignition and Compression Ignition - Gross Power Rating

3. Terminology

3.1 Definitions:

3.1.1 *blind reference oil, n*—a reference oil, the identity of which is unknown by the test facility. **D 5844**

3.1.1.1 *Discussion*—This is a coded reference oil that is submitted by a source independent from the test facility.

3.1.2 *blowby, n*—in internal combustion engines, the combustion products and unburned air-and-fuel mixture that enter the crankcase. **D 5302**

3.1.3 *calibrate, v*—to determine the indication or output of a measuring device with respect to that of a standard. **E 344**

3.1.4 *candidate oil, n*—an oil that is intended to have the performance characteristics necessary to satisfy a specification and is intended to be tested against that specification. **D 5844**

3.1.5 *heavy-duty, adj*—in internal combustion engine operation, characterized by average speeds, power output, and internal temperatures that are close to the potential maximums. **D 4485**

3.1.6 *heavy-duty engine, n*—in internal combustion engines, one that is designed to allow operation continuously at or close to its peak output. **D 4485**

3.1.7 *non-reference oil, n*—any oil other than a reference oil, such as a research formulation, commercial oil, or candidate oil. **D 5844**

3.1.8 *non-standard test, n*—a test that is not conducted in conformance with the requirements in the standard test method, such as running on an uncalibrated test stand, using different test equipment, applying different equipment assembly procedures, or using modified operating conditions. **D 5844**

3.1.9 *oxidation, n*—of engine oil, the reaction of the oil with an electron acceptor, generally oxygen, that can produce deleterious acidic or resinous materials often manifested as sludge formation, varnish formation, viscosity increase, or corrosion, or combination thereof. **Sub. B Glossary⁶**

3.1.10 *reference oil, n*—an oil of known performance characteristics, used as a basis for comparison. **D 5844**

3.1.10.1 *Discussion*—Reference oils are used to calibrate testing facilities, to compare the performance of other oils, or to evaluate other materials (such as seals) that interact with oils.

3.1.11 *sludge, n*—in internal combustion engines, a deposit, principally composed of insoluble resins and oxidation products from fuel combustion and lubricant, that does not drain from engine parts but can be removed by wiping with a cloth. **D 5302**

⁵ Available from Society of Automotive Engineers (SAE), 400 Commonwealth Dr., Warrendale, PA 15096-0001.

⁶ Available from the secretary of the ASTM D02.B0 Subcommittee.

⁴ Withdrawn.