



Designation: D6750 – 23

Standard Test Methods for Evaluation of Engine Oils in a High-Speed, Single-Cylinder Diesel Engine—1K Procedure (0.4 % Fuel Sulfur) and 1N Procedure (0.04 % Fuel Sulfur)¹

This standard is issued under the fixed designation D6750; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

INTRODUCTION

Portions of this test method are written for use by laboratories that make use of ASTM Test Monitoring Center (TMC)² services (see [Annex A1 – Annex A4](#)).

The TMC provides reference oils, and engineering and statistical services to laboratories that desire to produce test results that are statistically similar to those produced by laboratories previously calibrated by the TMC.

In general, the Test Purchaser decides if a calibrated test stand is to be used. Organizations such as the American Chemistry Council require that a laboratory utilize the TMC services as part of their test registration process. In addition, the American Petroleum Institute and the Gear Lubricant Review Committee of the Lubricant Review Institute (SAE International) require that a laboratory use the TMC services in seeking qualification of oils against their specifications.

The advantage of using the TMC services to calibrate test stands is that the test laboratory (and hence the Test Purchaser) has an assurance that the test stand was operating at the proper level of test severity. It should also be borne in mind that results obtained in a non-calibrated test stand may not be the same as those obtained in a test stand participating in the ASTM TMC services process.

Laboratories that choose not to use the TMC services may simply disregard these portions.

ASTM International policy is to encourage the development of test procedures based on generic equipment. It is recognized that there are occasions where critical/sole-source equipment has been approved by the technical committee (surveillance panel/task force) and is required by the test procedure. The technical committee that oversees the test procedure is encouraged to clearly identify if the part is considered critical in the test procedure. If a part is deemed to be critical, ASTM encourages alternative suppliers to be given the opportunity for consideration of supplying the critical part/component providing they meet the approval process set forth by the technical committee.

An alternative supplier can start the process by initiating contact with the technical committee (current chairs shown on ASTM TMC website). The supplier should advise on the details of the part that is intended to be supplied. The technical committee will review the request and determine feasibility of an alternative supplier for the requested replacement critical part. In the event that a replacement critical part has been identified and proven equivalent the sole-source supplier footnote shall be removed from the test procedure.

1. Scope*

1.1 These test methods cover the performance of engine oils intended for use in certain diesel engines. They are performed in a standardized high-speed, single-cylinder diesel engine by either the 1K (0.4 % mass fuel sulfur) or 1N (0.04 % mass fuel sulfur) procedure.³ *The only difference in the two test methods is the fuel used.* Piston and ring groove deposit-forming

¹ These test methods are under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.B0.02 on Heavy Duty Engine Oils.

Current edition approved July 1, 2023. Published July 2023. Originally approved in 2002. Last previous edition approved in 2019 as D6750 – 19^{ε1}. DOI: 10.1520/D6750-23.

² Until the next revision of this test method, the ASTM Test Monitoring Center will update changes in the test method by means of information letters. Information letters may be obtained from the ASTM Test Monitoring Center, 203 Armstrong Drive, Freeport, PA 16229. Attention: Director. This edition incorporates revisions in all information Letters through No. 23-1.

³ These 1K/1N test procedures were developed by Caterpillar Inc., P.O. Box 610, Mossville, IL 61552-0610.

*A Summary of Changes section appears at the end of this standard

tendency and oil consumption are measured. Also, the piston, the rings, and the liner are examined for distress and the rings for mobility. These test methods are required to evaluate oils intended to satisfy API service categories CF-4 and CH-4 for 1K, and CG-4 for 1N of Specification **D4485**.

1.2 These test methods, although based on the original Caterpillar 1K/1N procedures,³ also embody TMC information letters issued before these test methods were first published. These test methods are subject to frequent change. Until the next revision of these test methods, TMC will update changes in these test methods by the issuance of information letters which shall be obtained from TMC (see **Annex A1 – Annex A4**).

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3.1 *Exception*—Where there is no direct SI equivalent such as screw threads, national pipe threads/diameters, tubing size, or single source equipment specified. Also Brake Specific Fuel Consumption is measured in kilograms per kilowatthour.

1.4 The following is the Table of Contents:

	Section
Introduction	
Scope	1
Referenced documents	2
Terminology	3
Summary of Test Methods	4
Significance and Use	5
Apparatus	6
General Laboratory Requirements	6.1
Test Engine	6.2
Test Engine Accessories and Parts	6.3
Reagents and Materials	7
Test Oil Sample Requirements	8
Preparation of Apparatus	9
Engine Inspection	9.1
Engine Pre-Test Lubrication System Flush	9.2
Engine Pre-Test Measurements and Inspections	9.3
Engine Assembly	9.4
Pressure Testing of Fuel System Assembly	9.5
Calibration of Engine Test Stand	10
General Requirements and Frequency of Calibration	10.1
Runs	10.2
Specified Test Parameters	10.3
Calibration Test Acceptance Criteria	10.4
Action on Rejection of Calibration Test	10.5
Test Numbering	10.6
Reference Oils	10.7
Severity Adjustments	10.8
Engine Operating Procedure	11
Engine Run-In	11.1
Cool-Down Procedure	11.2
Warm-Up Procedure	11.3
Operating Conditions and Oil Additions	11.4
Measurement of Oil Consumption	11.5
Sampling Used Oil	11.6
Shutdowns, Lost Time and Off Tolerance Conditions	11.7
Recording of Exhaust Temperature	11.8
Air-Fuel Ratio Measurement	11.9
Recording of Engine Conditions	11.10
Humidity Requirements/Calibration/Measurement	11.11
Inspections, Photographs and Measurements	12
Reference to Reporting Form	12.1
Pre-Test Measurements of Engine Parts	12.2
Post-Test Information	12.3
Oil Inspections	12.4
Report	13
General Directions	13.1
Electronic Transmission of Test Results (Optional)	13.12

Reporting Calibration Test Results	13.13
Precision and Bias	14
Keywords	15

ANNEXES

ASTM Test Monitoring Center Organization	Annex A1
ASTM Test Monitoring Center: Calibration Procedures	Annex A2
ASTM Test Monitoring Center: Maintenance Activities	Annex A3
ASTM Test Monitoring Center: Related Information	Annex A4
Specifications for Test Engine and Engine Build	Annex A5
Intake Air System Details	Annex A6
Exhaust System Details	Annex A7
Cooling System Details	Annex A8
Oil System Modifications and Instrument Locations	Annex A9
Other Pressure and Temperature Measurement Locations	Annex A10
Oil Consumption Linear Regression Method	Annex A11
Test Fuel Specifications	Annex A12
Lubrication System, Flush Apparatus and Procedure	Annex A13
Engine Operating Conditions	Annex A14
Procedure for Rating Piston and Liner	Annex A15
Calculation of Percent Offset and Percent Deviation	Annex A16
1K/1N Test Reporting	Annex A17
Parts List by Part Number (P/N) and Warranty	Annex A18
Safety Precautions	Annex A19

APPENDIXES

Humidity Data	Appendix X1
Statistical Equations for Mean and Standard Deviation	Appendix X2
Examples of Forms for Reporting	Appendix X3
Optional Recording of Oil Pass Limits	Appendix X4

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.* Specific precautionary statements appear throughout the text. Being engine tests, these test methods do have definite hazards that shall be met by safe practices (see **Annex A19** on Safety Precautions).

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:⁴

- D86** Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure
- D93** Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D97** Test Method for Pour Point of Petroleum Products
- D130** Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D235** Specification for Mineral Spirits (Petroleum Spirits) (Hydrocarbon Dry Cleaning Solvent)
- D287** Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer/Method)
- D445** Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)

⁴ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.