



Designation: D7188 – 05 (Reapproved 2019)

Standard Terminology for Printing Inks, Materials, and Processes¹

This standard is issued under the fixed designation D7188; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This terminology standard covers terms used in the description of printing inks, printing materials, and printing processes.

1.2 This terminology standard does not include definitions related to Print Problems (see Terminology D6488).

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

- D16 Terminology for Paint, Related Coatings, Materials, and Applications
- D1316 Test Method for Fineness of Grind of Printing Inks By the NPIRI Grindometer
- D1535 Practice for Specifying Color by the Munsell System
- D2066 Test Methods for Relative Tinting Strength of Paste-Type Printing Ink Dispersions
- D3732 Practice for Reporting Cure Times of Ultraviolet-Cured Coatings
- D4040 Test Method for Rheological Properties of Paste Printing and Vehicles by the Falling-Rod Viscometer
- D4302 Specification for Artists' Oil, Resin-Oil, and Alkyd Paints

¹ This terminology is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.56 on Printing Inks.

Current edition approved Jan. 1, 2019. Published January 2019. Originally approved in 2005. Last previous edition approved in 2010 as D7188 – 05 (2010). DOI: 10.1520/D7188-05R19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- D4361 Test Method for Apparent Tack of Printing Inks and Vehicles by a Three-Roller Tackmeter
 - D4449 Test Method for Visual Evaluation of Gloss Differences Between Surfaces of Similar Appearance
 - D5010 Guide for Testing Printing Inks and Related Materials (Withdrawn 2017)³
 - D5181 Test Method for Abrasion Resistance of Printed Matter by the GA-CAT Comprehensive Abrasion Tester
 - D5383 Practice for Visual Determination of the Lightfastness of Art Materials by Artists and Art Technologists
 - D5403 Test Methods for Volatile Content of Radiation Curable Materials
 - D5909 Test Method for Drying Time of Oxidative-Drying Printing Inks by Squalene Resistance
 - D6488 Terminology Relating to Print Problems
 - D6493 Test Methods for Softening Point of Hydrocarbon Resins and Rosin Based Resins by Automated Ring-and-Ball Apparatus
 - D6687 Guide for Testing Printing Ink Vehicles and Components Thereof
 - E430 Test Methods for Measurement of Gloss of High-Gloss Surfaces by Abridged Goniophotometry
- #### 2.2 Other Documents:
- NAPIM: National Association of Printing Ink Manufacturers, 5th ed. 1988⁴
 - Kipphan: *Handbook of Print Media Technologies and Production Methods*, Kipphan, Helmut: Springer 2001⁵

3. Significance and Use

3.1 A common set of definitions is essential to improve communication and avoid misunderstanding among ink makers, paper makers, and printers.

3.2 Definitions that are verbatim from one of the referenced sources are indicated by giving the acronym of the organization or the author of the book at the end of the definition.

4. Terminology

4.1 Definitions:

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Available from National Association of Printing Ink Manufacturers, 581 Main St., 5th Fl., Woodbridge, NJ 07095, <http://www.napim.org>.

⁵ Available from Springer Nature, <http://www.springer.com>.

abrasion resistance, *n*—(1) the ability of a coating to resist being worn away and to maintain its original appearance and structure when subjected to rubbing, scraping, or wear. **D16**
(2) resistance against the act of scraping, smudging, or rubbing off. **D5181**

(3) ability to withstand the effects of repeated rubbing and scuffing. **NAPIM**

abrasiveness, *n*—(1) the degree to which a product tends to cause abrasion by the act of rubbing or scraping. **D5181**

(2) the tendency of a substance to wear or scratch other surfaces with which it is in contact. **NAPIM**

absorbency, *n*—the tendency of a porous material, such as paper, to take up liquids or vapors. **NAPIM**

absorption, *n*—soaking in or penetration of liquid components of the ink into the pores of an absorbent substrate (a type of physical drying, like evaporation). **Kipphan**

‘across-machine’ direction, *n*—the perpendicular to ‘with-machine’ direction, referring to a substrate and its passage through printing machinery.

additive, *n*—a substance added in small quantities to another substance, usually to improve properties; sometimes called a modifier (for example, a drier, mildewcide, etc.). **D16**

additive primary colors, *n*—red, green, and blue. **NAPIM**

DISCUSSION—Mixing lights of these colors together can produce a large gamut of colors. When mixed in equal amounts, they produce the sensation of white light.

adhesion, *n*—the tendency of a material to bond to another material, as in the bonding of a printing ink to a substrate.

adhesion promoter, *n*—a material built into the binder or added to the ink to form primary bonds to either the substrate or the previously applied coating, with the specific aim of improving the dry or wet adhesion, or both.

adsorption, *n*—the adhesion of an extremely thin layer of material to the surface with which it is in contact. **NAPIM**

after-tack, *n*—the tendency of a printed surface to remain sticky to the touch even when the ink has completed its drying process.

agglomerate, *n*—a cluster of pigment aggregates that can be broken down by appropriate dispersion and milling operations during ink manufacture.

aggregate, *n*—a cluster of primary pigment particles that cannot be broken down by dispersion and milling operations during ink manufacture.

alkyd, *n*—a group of synthetic resins formed by condensations of polybasic acids with polyhydric alcohols, and modified with drying oils for printing ink use. **NAPIM**

aluminum ink, *n*—see **silver ink**.

aniline ink, *n*—early name for rubber plate printing fluid (flexographic) ink. **NAPIM**

aniline point, *n*—the minimum temperature at which a hydrocarbon solvent is completely soluble in an equal volume of freshly distilled aniline. **NAPIM**

DISCUSSION—Below this point, the mixture is cloudy and separates into two layers. It is used as a measure of solvent power of hydrocarbon solvents.

aniline printing, *n*—an earlier name for flexography, based on the use of the aniline inks that were initially used. **Kipphan**

anilox roller, *n*—an engraved metering cylinder used in flexo presses to transfer a controlled film of ink to the printing plate.

antiskinning agents, *n*—chemical substances that retard the skin formation on the surface of an oxidizable oil or ink (frequently antioxidants). **NAPIM**

apparent tack, *n*—a measure of the force required to split an ink film at the out-running nip of a pair of rollers under a specific set of conditions.

ball mill, *n*—a dispersion device comprised of a rotating cylinder containing balls which cascade; used to disperse a pigment in a vehicle by impact and attrition as the cylinder revolves. **NAPIM**

barrier coating, *n*—the coating applied to a substrate to make it resistant to the permeation of moisture vapor, gases, water, or other liquids including oils. **NAPIM**

base, *n*—*in ink manufacture*, a dispersion of very high pigment-to-binder ratio containing usually only one pigment (or dye) dispersed in a vehicle and subsequently mixed with polymers, solvents, and additives to produce the finished ink. **NAPIM**

basis weight, *n*—the weight in pounds of a ream (500 sheets) of paper cut to a given standard size for that grade. **NAPIM**

DISCUSSION—For example, 500 sheets 25 by 38 of 80-lb. coated for book papers will weigh eighty pounds.

batch, *n*—a discrete quantity of manufactured ink or coating produced by following a formula to completion.

bimetal plate, *n*—*in lithography*, a plate in which the image area is copper or brass and the non-image area is aluminum, stainless steel, or chromium. **NAPIM**

binder, *n*—the components in an ink film which hold the pigment to the printed surface. **NAPIM**

blanc fixe, *n*—precipitated barium sulphate used as a semi-transparent extender in printing inks. **NAPIM**

blanket, *n*—(1) *in offset lithography*, a fabric coated with natural or synthetic rubber which is clamped around the blanket cylinder and which transfers the ink from the press plate to the paper. **NAPIM**

(2) the sheet of elastomer-coated fabric or equivalent placed on the blanket cylinder to receive ink from the plate and offset it to the sheet or web on the impression cylinder.

blanket cylinder, *n*—a rigid roller to which a rubber coating fabric is attached.