



# Standard Practice for Control of Respiratory Hazards in the Metal Removal Fluid Environment<sup>1</sup>

This standard is issued under the fixed designation E2889; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

## 1. Scope\*

1.1 This practice sets forth guidelines to control respiratory hazards in the metal removal environment.

1.2 This practice does not include prevention of dermatitis, which is the subject of Practice E2693, but it does adopt a similar systems management approach with many control elements in common.

1.3 This practice focuses on employee exposure via inhalation of metal removal fluids and associated airborne agents.

1.4 Metal removal fluids used for wet machining operations (such as cutting, drilling, milling, or grinding) that remove metal to produce the finished part are a subset of metalworking fluids. This practice does not apply to other operations (such as stamping, rolling, forging, or casting) that use metalworking fluids other than metal removal fluids. These other types of metalworking fluid operations are not included in this document because of limited information on health effects, including epidemiology studies, and on control technologies. Nonetheless, some of the exposure control approaches and guidance contained in this document may be useful for managing respiratory hazards associated with other types of metalworking fluids.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee E34 on Occupational Health and Safety and is the direct responsibility of Subcommittee E34.50 on Health and Safety Standards for Metal Working Fluids.

Current edition approved Oct. 1, 2023. Published October 2023. Originally approved in 2012. Last previous edition approved in 2017 as E2889 – 12 (2017). DOI: 10.1520/E2889-23.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

- D1356 Terminology Relating to Sampling and Analysis of Atmospheres
- D2881 Classification for Metalworking Fluids and Related Materials
- D7049 Test Method for Metalworking Fluid Aerosol in Workplace Atmospheres
- E1302 Guide for Acute Animal Toxicity Testing of Water-Miscible Metalworking Fluids
- E1370 Guide for Air Sampling Strategies for Worker and Workplace Protection
- E1497 Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids
- E1542 Terminology Relating to Occupational Health and Safety
- E2144 Practice for Personal Sampling and Analysis of Endotoxin in Metalworking Fluid Aerosols in Workplace Atmospheres
- E2148 Guide for Using Documents Related to Metalworking or Metal Removal Fluid Health and Safety
- E2169 Practice for Selecting Antimicrobial Pesticides for Use in Water-Miscible Metalworking Fluids
- E2275 Practice for Evaluating Water-Miscible Metalworking Fluid Bioresistance and Antimicrobial Pesticide Performance
- E2523 Terminology for Metalworking Fluids and Operations
- E2563 Practice for Enumeration of Non-Tuberculosis *Mycobacteria* in Aqueous Metalworking Fluids by Plate Count Method
- E2564 Practice for Enumeration of *Mycobacteria* in Metalworking Fluids by Direct Microscopic Counting (DMC) Method
- E2657 Practice for Determination of Endotoxin Concentrations in Water-Miscible Metalworking Fluids
- E2693 Practice for Prevention of Dermatitis in the Wet

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard

## Metal Removal Fluid Environment

**E2694** Test Method for Measurement of Adenosine Triphosphate in Water-Miscible Metalworking Fluids

**E3265** Guide for Evaluating Water-Miscible Metalworking Fluid Foaming Tendency

2.2 *OSHA (U.S. Occupational Safety and Health Administration) Standards:*<sup>3</sup>

29 CFR 1910.132 Personal Protective Equipment

29 CFR 1910.134 Use of Respiratory Protection in the Workplace

29 CFR 1010.1020 Access to Employee Exposure and Medical Records

29 CFR 1910.1048 Formaldehyde

29 CFR 1910.1200 Hazard Communication

2.3 *EPA (U.S. Environmental Protection Agency) Standards:*<sup>4</sup>

40 CFR 156 Labeling Requirements for Pesticides and Devices

2.4 *Other Documents:*

**ANSI Technical Report B11 TR 2-1997** Mist Control Considerations for the Design, Installation and Use of Machine Tools Using Metalworking Fluids<sup>5</sup>

**National Center for Manufacturing Sciences** Metal Working Fluid Optimization Guide<sup>6</sup>

**ACGIH** Industrial Ventilation: A Manual of Recommended Practice for Design<sup>7</sup>

**ACGIH** Industrial Ventilation: A Manual of Recommended Practice for Operation and Maintenance<sup>8</sup>

**NIOSH** Criteria for a Recommended Standard: Occupational Exposure to Metalworking Fluids<sup>9</sup>

**OSHA** Metalworking Fluids: Safety and Health Best Practices Manual<sup>10</sup>

**NIOSH Method 5524** Metalworking Fluids (MWF) All Categories<sup>11</sup>

## 3. Terminology

3.1 For definitions and terms relating to this guide, refer to Terminologies **D1356**, **E1542**, and **E2523**.

3.2 *Definitions of Terms Specific to This Standard:*

<sup>3</sup> Available from United States Government Printing Office, Washington, DC 20402 or at eCFR, 29 CFR Part 1910, <https://www.ecfr.gov/current/title-29/subtitle-B/chapter-XVII/part-1910?toc=1>.

<sup>4</sup> Available from United States Government Printing Office, Washington, DC 20402 or at eCFR, 40 CFR Part 156, <https://www.ecfr.gov/current/title-40/chapter-I/subchapter-E/part-156>.

<sup>5</sup> Available from American National Standards Institute (ANSI); see B11 Standards, Inc. ([www.ansi.org](http://www.ansi.org)).

<sup>6</sup> Available from National Center for Manufacturing Sciences, Report 0274RE95, 3025 Boardwalk, Ann Arbor, MI 48018.

<sup>7</sup> Available from ACGIH at <https://portal.acgih.org/s/store#/store/browse/detail/a158a0000CgqcfAAB>.

<sup>8</sup> Available from ACGIH at <https://portal.acgih.org/s/store#/store/browse/detail/a154W00000BOaw1QAD>.

<sup>9</sup> Available from National Institute for Occupational Safety and Health (NIOSH) at <https://www.cdc.gov/niosh/docs/98-102/>.

<sup>10</sup> Available from U.S. Occupational Health and Safety Administration (OSHA) at <https://www.osha.gov/metalworking-fluids/manual>.

<sup>11</sup> Available from National Institute for Occupational Safety and Health (NIOSH) at <https://www.cdc.gov/niosh/docs/2003-154/pdfs/5524.pdf>.

3.2.1 *dilution ventilation, n*—referring to the supply and exhaust of air with respect to an area, room, or building; the dilution of contaminated air with uncontaminated air for the purpose of controlling potential health hazards, fire and explosion conditions, odors, and nuisance-type contaminants. From Industrial Ventilation: A Manual of Recommended Practice.

3.2.2 *extractable mass, n*—the material removed by liquid extraction of the sampling filter using a mixed-polarity solvent mixture as described in Test Method **D7049** or NIOSH Method 5524.

3.2.2.1 *Discussion*—This mass is an approximation of the metal removal fluid portion of the workplace aerosol.

3.2.3 *metal removal fluid (MRF), n*—any fluid in the subclass of metalworking fluids used to cut or otherwise take away material or piece of stock. **E2148**

3.2.3.1 *Discussion*—Metal removal fluids include straight or neat oils (Classification **D2881**) not intended for further dilution with water, and water-miscible soluble oils, semisynthetics, and synthetics, which are intended to be diluted with water before use. Metal removal fluids become contaminated during use in the workplace with a variety of workplace substances including, but not limited to: abrasive particles, tramp oils, cleaners, dirt, metal fines and shavings, dissolved metal and hard water salts, bacteria, fungi, microbiological decay products, and waste. These contaminants can cause changes in the lubricity and cooling ability of the metal removal fluid as well as have the potential to adversely affect the health and welfare of employees in contact with the contaminated metal removal fluid. **E2148**

3.2.4 *metal removal fluid aerosol, n*—aerosol generated by operation of the machine tool itself as well as from circulation and filtration systems associated with wet metal removal operations and may include airborne contaminants of microbial origin.

3.2.4.1 *Discussion*—Metal removal aerosol does not include background aerosol in the workplace atmosphere, which may include suspended insoluble particulates.

3.2.5 *total particulate matter, n*—the mass of material sampled through the 4 mm inlet of a standard 37 mm filter cassette when operated at 2.0 L/min, as described in Test Method **D7049**.

3.2.5.1 *Discussion*—As defined in Test Method **D7049**, total particulate matter is not a measure of the inhalable or thoracic particulate mass.

## 3.3 Acronyms:

3.3.1 *GHS, n*—globally harmonized system

3.3.1.1 *Discussion*—GHS is an acronym for the Globally Harmonized System of Classification and Labeling of Chemicals.

## 4. Significance and Use

4.1 Exposure to aerosols in the industrial metal removal environment has been associated with adverse respiratory effects.

4.2 Use of this practice will mitigate occupational exposure and effects of exposure to aerosols in the metal removal environment.