



Designation: F2961 – 22

Standard Test Method for Characterizing Gripping Performance of Gloves Using a Torque Meter¹

This standard is issued under the fixed designation F2961; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is used for evaluating how gloves affect an individual wearer's ability to grip onto a hard surface object.

1.1.1 This test method establishes procedures for measuring the maximum torque that can be attained by an individual's bare hand as compared to the maximum torque that is attained by the same individual wearing a glove. The torque is applied to a vertically mounted pole attached to a torque meter.

1.2 This test method is suitable for evaluating gloves and other forms of hand protection that require the wearer to maintain a secure hold on objects.

1.3 This test method does not address all effects of wearing gloves on hand functions. Other test methods include those for evaluating the effect of wearing gloves on dexterity, tactility, and other aspects of functional performance.

1.4 It is the responsibility of the test laboratory to obtain the necessary and appropriate approval(s) required by their institution for conducting tests using human subjects.

1.5 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.7 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

¹ This test method is under the jurisdiction of ASTM Committee F23 on Personal Protective Clothing and Equipment and is the direct responsibility of Subcommittee F23.60 on Human Factors.

Current edition approved Feb. 1, 2022. Published March 2022. Originally approved in 2014. Last previous edition approved in 2015 as F2961 – 15. DOI: 10.1520/F2961-22.

2. Referenced Documents

2.1 ASTM Standards:²

D1776/D1776M Practice for Conditioning and Testing Textiles

E177 Practice for Use of the Terms Precision and Bias in ASTM Test Methods

E691 Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method

F1494 Terminology Relating to Protective Clothing

2.2 NFPA Standards:³

NFPA 1971 Standard on Protective Ensembles for Structural Fire Fighting and Proximity Fire Fighting

3. Terminology

3.1 For definitions of other protective clothing-related terms used in this test method, refer to Terminology F1494.

4. Summary of Test Method

4.1 The maximum torque applied to a vertically oriented cylindrical rod is measured without gloves and then later while wearing gloves. The bare hand maximum torque is compared to the gloved hand maximum torque in terms of a percentage. This percentage is useful in determining if a glove enhances or decreases an individual's ability to grip a hard object.

5. Significance and Use

5.1 This test method is intended to provide a quantitative measurement of wearing gloves on an individual's ability to grip a solid object and twist in a defined direction. The gripping performance may be different if twisted in the opposing direction or if pushing or pulling on a solid object while gripping.

5.2 This method was originally developed to help understand how materials and construction of firefighting gloves affected grip. Methods available at the time showed very little

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.

statistical difference between a wide range of gloves, including many NFPA 1971 compliant firefighting gloves and also non-compliant gloves used in other applications. This method was shown to have less subject-to-subject variability and a greater range of measured grip than previous tests.⁴

5.3 It is possible to apply this test method to other types of gloves, other than structural firefighting protective gloves. Evaluate the relevance of this test method by examining the particular application of the gloves for end user gripping capability. In addition, understand how this test method ranks gloves in comparison with end user perceptions.

5.4 This test method does not discriminate all glove effects on wearer hand function, nor does it apply to all glove types and applications. Consider additional evaluations or tests representative of the glove use applications performed to determine the overall impact of gloves on wearer hand functions.

6. Apparatus

6.1 *Testing Apparatus*—The device used to characterize the gripping performance of gloves consists of a torque meter with adjustable rod holder and a smooth acrylic cylindrical rod (Fig. 1). The rod is secured tightly in the adjustable rod holder attached to the torque meter.

6.2 Use a torque meter capable of meeting the following requirements:

6.2.1 Measuring 0 to 10.0 ± 0.5 N·m (88.5 ± 4.5 lb-in.).

6.2.1.1 A torque meter with a higher measuring range is allowed provided it still has an accuracy of ± 0.5 N·m (± 4.5 lb-in.).

6.2.2 Able to be fastened in place or heavy enough to be immobile during testing.

6.2.3 Able to measure torque in either a clockwise or counter-clockwise direction.

6.2.4 Fitting with an adjustable rod holder fixed to the upper surface of the meter.

6.2.4.1 The rod holder has four metal pins protruding upwards from the surface. Use 10 mm diameter pins that protrude 30 mm from the surface of the holder.

(1) Cover the metal pins with a rubber material that is between 2.5 and 3.0 mm thick.

6.3 Use transparent cast acrylic rod meeting the following requirements:

6.4 Measures 600 mm (24 in.) in length and has a diameter of 41.5 mm (1.625 in.).

6.4.1 Has a surface roughness value of 0.10 ± 0.05 μ m (4 ± 2 μ in.) and is free of visual scratches and blemishes.

6.4.2 Use an acrylic rod with four grooves cut into the bottom of the rod. Grooves should match the size of the pins with rubber covering.

6.4.2.1 Fig. 2 shows an example of a rod cut with grooves at the bottom.



FIG. 1 Acrylic Rod Attached to a Torque Meter

7. Sampling, Test Specimens, and Test Units

7.1 Use a minimum of three glove specimens for testing each model or type of glove.

7.1.1 Use right-handed glove specimens for right-hand dominant test subjects and left-handed glove specimens for left-hand dominant test subjects.

7.1.2 Each glove specimen shall be tested by a different human subject.

7.2 Each glove specimen shall be tested in a new, as-distributed condition.

7.2.1 Do not use glove specimens that are treated, broken-in, or conditioned in any manner other than specified in this test method prior to their evaluation unless otherwise specified.

8. Conditioning

8.1 Condition all glove specimens at a temperature of 21 ± 3 °C (70 ± 5 °F) and a relative humidity of 65 ± 5 %, until

⁴ Ross, Barker, Watkins, and Deaton, "Methods for Measuring the Grip Performance of Structural Firefighting Gloves," *Performance of Protective Clothing and Equipment: Emerging Issues and Technologies*, ASTM STP 1544, Vol 9, A. Shepherd Ed., ASTM International, West Conshohocken, PA, 2012.