

Measurement of fluid flow in closed conduits —

Part 1: Pressure differential devices —

Section 1.2 Specification for square-edged orifice plates and nozzles (with drain holes, in pipes below 50 mm diameter, as inlet and outlet devices) and other orifice plates

UDC 532.542:532.575.52

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Industrial-process Measurement and Control Standards Policy Committee (PCL/-) to Technical Committee PCL/2, upon which the following bodies were represented:

- British Compressed Air Society
- British Gas plc
- Department of Energy (Gas and Oil Measurement Branch)
- Department of Trade and Industry (National Engineering Laboratory)
- Electricity Supply Industry in England and Wales
- Energy Industries Council
- GAMBICA (BEAMA Ltd.)
- Institute of Measurement and Control
- Institute of Petroleum
- Institute of Trading Standards Administration
- Institution of Gas Engineers
- Institution of Mechanical Engineers
- Water Authorities' Association

The following bodies were also represented in the drafting of the standard, through subcommittees and panels:

- Engineering Equipment and Materials Users' Association
- Institution of Water and Environmental Management (IWEM)
- United Kingdom Offshore Operators' Association

This British Standard, having been prepared under the direction of the Industrial-process Measurement and Control Standards Policy Committee, was published under the authority of the Board of BSI and comes into effect on 29 September 1989

© BSI 01-2000

First published as part of BS 1042-1 February 1943
First revision September 1964
First published as BS 1042-1.2 March 1984
First revision September 1989

The following BSI references relate to the work on this standard:
Committee reference PCL/2
Draft for comment 87/21719 DC

ISBN 0 580 17415 8

Amendments issued since publication

Amd. No.	Date of issue	Comments
8191	July 1994	Indicated by a sideline in the margin