

Radio-frequency connectors —

**Part 7: R.F. coaxial connectors with
inner diameter of outer
conductor 9,5 mm (0,374 in) with
bayonet lock —
Characteristic impedance 50 ohms
(Type C) —**

**(Implementation of CENELEC
HD 134.7 S2)**

ICS 33.120.30

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by Technical Committee EPL/46, Cables, wires and waveguides, RF connectors and accessories for communication and signalling, to Subcommittee EPL/46/2, RF connectors and waveguides, on which the following bodies were represented:

- AEA Technology
- BEAMA Electrical Cable & Conductor Accessory Manufacturers
- British Non-Ferrous Metals Federation
- British Telecommunications plc
- Federation of the Electronics Industry
- Ministry of Defence
- National Supervisory Inspectorate
- Society of Cable Television Engineers

This British Standard, having been prepared under the direction of the Electrotechnical Sector Board, was published under the authority of the Standards Board and comes into effect on 15 December 1996

© BSI 12-1998

The following BSI references relate to the work on this standard:
Committee reference EPL/46/2
Draft announced in *BSI Update* September 1996

ISBN 0 580 26611 7

Amendments issued since publication

Amd. No.	Date	Comments