

Rigid polyurethane (PUR) and polyisocyanurate (PIR) foam when dispensed or sprayed on a construction site —

**Part 1: Specification for sprayed foam
thermal insulation applied externally**

Confirmed December 2009

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Plastics and Rubber Standards Policy Committee (PRM/-) to Technical Committee PRM/72, upon which the following bodies were represented:

- Association of Building Component Manufacturers
- Brick Development Association
- British Board of Agrement
- British Plastics Federation
- British Rigid Urethane Foam Manufacturers' Association
- Calcium Silicate Brick Association Limited
- Cavity Foam Bureau
- Department of the Environment (Building Research Establishment)
- Department of the Environment (Construction Directorate)
- Engineering Equipment and Materials Users' Association
- European Phenolic Foam Association
- Flat Roofing Contractors' Advisory Board
- Ministry of Defence
- National Federation of Roofing Contractors
- National House-building Council
- Polyethylene Foam Insulation Association
- Royal Institute of British Architects

The following bodies were also represented in the drafting of the standard, through subcommittees and panels:

- British Ceramic Research Ltd.
- British Urethane Foam Contractors' Association (BUFCA)
- Department of the Environment
- RAPRA Technology Ltd.

This British Standard, having been prepared under the direction of the Plastics and Rubber Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 15 March 1994

© BSI 07-1999

First published June 1989
Second edition March 1994

The following BSI references relate to the work on this standard:
Committee reference PRM/72
Draft for comment 92/46319 DC

ISBN 0 580 22807 X

Amendments issued since publication

Amd. No.	Date	Comments