

CONFIRMED  
DECEMBER 2007

**BS 5627 : 1984**

UDC 696.141.1 : 621.643.4—036.5

---

**British Standard Specification for**

**Plastics connectors for use with**

**horizontal outlet vitreous china WC pans**

---

Raccordements en plastique pour cuvettes de WC en porcelaine vitreuse  
à sortie horizontale — Spécifications

Kunststoffverbindungsstücke für WC-Becken aus Sanitärporzellan mit  
waagrechtem Abfluß

Contents

|                                                     |                    |
|-----------------------------------------------------|--------------------|
|                                                     | Page               |
| Foreword                                            | Inside front cover |
| Committees responsible                              | Back cover         |
| <b>Specification</b>                                |                    |
| <b>Section one. General</b>                         |                    |
| 1. Scope                                            | 1                  |
| 2. Seals for WC spigots and pipework                | 1                  |
| 3. Freedom from defects                             | 1                  |
| 4. Marking                                          | 1                  |
| <b>Section two. Materials</b>                       |                    |
| 5. Ethylene vinyl acetate connectors (EVA)          | 1                  |
| 6. Polypropylene copolymer connectors (PP)          | 1                  |
| 7. Acrylonitrile butadiene styrene connectors (ABS) | 2                  |
| <b>Section three. Performance</b>                   |                    |
| 8. Seals for WC spigots and pipework                | 2                  |
| 9. Functional test requirements                     | 2                  |
| 10. Frequency of testing                            | 2                  |
| <b>Section four. Dimensions</b>                     |                    |
| 11. General                                         | 2                  |
| 12. Minimum wall thickness                          | 4                  |

|                                                                                           |   |
|-------------------------------------------------------------------------------------------|---|
| <b>Appendices</b>                                                                         |   |
| A. Determination of vinyl acetate in ethylene/vinyl acetate copolymers (reference method) | 5 |
| B. Environmental stress cracking test                                                     | 5 |
| C. Impact test (PP)                                                                       | 6 |
| D. Impact resistance of fittings (ABS)                                                    | 6 |
| E. Water test for pan connectors                                                          | 8 |
| F. Air pressure test for pan connectors                                                   | 8 |
| <b>Tables</b>                                                                             |   |
| 1. Testing schedule                                                                       | 2 |
| 2. Test portion of dry copolymer                                                          | 5 |
| <b>Figures</b>                                                                            |   |
| 1. 90 ° WC bend to convert to S or turned P trap with 110 mm o.d. 170 spigot min.         | 3 |
| 2. 90 ° WC bend to convert to S or turned P trap with 80 mm min. i.d. 230 spigot min.     | 3 |
| 3. 14 ° WC bend with 110 mm o.d. outlet                                                   | 3 |
| 4. 14 ° WC bend with 80 mm min. i.d. outlet                                               | 3 |
| 5. 14 ° WC bend socket to socket                                                          | 4 |
| 6. 90 ° WC bend socket to socket                                                          | 4 |
| 7. Socket details                                                                         | 4 |
| 8. Environmental stress cracking test apparatus                                           | 6 |
| 9. Apparatus for impact test (PP)                                                         | 7 |
| 10. Test piece                                                                            | 7 |
| 11. Illustration of water test                                                            | 8 |
| 12. Illustration of air test                                                              | 9 |

Foreword

This revision of this British Standard has been prepared under the direction of the Building Services Standards Committee to specify plastics connectors for use with horizontal outlet WC pans manufactured to the requirements of BS 5503 : Parts 1 and 2 or to BS 5504 : Parts 1, 2 and 3 to enable their connection to new and existing drainage systems. It supersedes BS 5627 : 1978 which is withdrawn.

Requirements are given for connectors manufactured from several different plastics materials and because of

the varied nature of plastics materials in current use it has been decided to deal with each particular material in a separate clause. Thus connectors have to meet the requirements of the particular material clause as well as the other requirements.

Attention is drawn to BS 4514 in which connectors manufactured from unplasticized PVC are specified, and in which cross reference is made to this standard.

**Compliance with a British Standard does not of itself confer immunity from legal obligations.**