



BS 6431 : Part 3 : Section 3.1 : 1986
EN 186-1

UDC 691.433-413-033.6:666.75-184.2

© British Standards Institution. No part of this publication may be photocopied or otherwise reproduced without the prior permission in writing of BSI

British Standard

Ceramic floor and wall tiles

Part 3. Extruded ceramic tiles with a water absorption of
 $3\% < E \leq 6\%$

Group Alla. Section 3.1 Specification for general products

Carreaux et dalles céramiques pour sols et murs

Partie 3. Carreaux et dalles céramiques étirés à absorption d'eau $3\% < E \leq 6\%$.

Groupe Alla. Section 3.1

Keramische Fliesen und Platten für Bodenbeläge und Wandbekleidungen

Teil 3. Stranggepreßte keramische Fliesen und Platten mit einer Wasseraufnahme von $3\% < E \leq 6\%$.

Gruppe Alla. Abschnitt 3.1

The European Standard EN 186-1 has the status of a British Standard.

British Standards Institution

BS 6431 : Part 3 : Section 3.1 : 1986

Contents

	Page		Page
National foreword		Inside front cover	
Brief history		2	
National appendix A		Inside back cover	
National appendix B		Inside back cover	
Cooperating organizations		Back cover	
		Tables	
		1 Modular preferred sizes for split tiles	4
		2 Non-modular sizes for split tiles	4
		3 Modular preferred sizes for quarry tiles	5
		4 Non-modular sizes for quarry tiles	5
		5 (Requirements)*	6
Specification		Figures	
1 Scope and field of application	3	1 Split tile	3
2 References	3	2 Quarry tile	4
3 Description	3		
4 Shapes and sizes	3		
5 Requirements	6		
6 Marking and designation	7		
7 Ordering	7		

National foreword

This Section of this British Standard has been prepared under the direction of the Clay Products Standards Committee and is the English language version of EN 186-1 'Ceramic tiles. Extruded ceramic tiles with a water absorption of $3\% < E \leq 6\%$ (Group IIa) Part 1' published by the European Committee for Standardization (CEN).

EN 186-1 was produced as a result of international discussion in which the UK took an active part.

Extruded ceramic tiles having the same water absorption characteristics but with a different performance in respect of modulus of rupture, scratch hardness and resistance to deep abrasion of unglazed tiles (see clause 1) are covered in Part 3 : Section 3.2 of this standard.

Attention is drawn to the use in this standard of the comma as a decimal marker. This is to accord with European practice, but it should be noted that it is current practice in British Standards to use a full point on the baseline as a decimal marker.

Additional information. When marking or specifying a product (see 6.1 and 6.2) the manufacturer may mark or specify by reference to either the European standard or the British Standard.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

* Untitled in the text of EN 186-1.