

Three phase oil-immersed distribution transformers, 50 Hz, from 50 to 2500 kVA with highest voltage for equipment not exceeding 36 kV —

**Part 2: Distribution transformers with
cable boxes on the high voltage and/or
low voltage side —**

Section 2.1 General requirements —

**(Implementation of CENELEC
HD 428.2.1 S1:1994)**

UDC 621.314.212

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee PEL/14, Power transformers, upon which the following bodies were represented:

- Association of Consulting Engineers
- BEAMA Ltd. (Transmission and Distribution Association)
- British Cable Makers' Confederation
- British Pump Manufactures' Association
- British Railways Board
- Electricity Association
- Institution of Plant Engineers
- Transmission and Distribution Association (BEAMA Ltd.)

This British Standard, having been prepared under the direction of the Electrotechnical Sector Board, was published under the authority of the Standards Board and comes into effect on 15 September 1995

© BSI 07-1999

The following BSI references relate to the work on this standard:
Committee reference PEL/14
Draft for comment 92/29074 DC

ISBN 0 580 24718 X

Amendments issued since publication

Amd. No.	Date	Comments