



BSI Standards Publication

Aerospace series — Rotorcraft constant wear lifejackets — Requirements, testing and marking

National foreword

This British Standard is the UK implementation of EN 4862:2023.

The UK participation in its preparation was entrusted to Technical Committee ACE/1/-/3, Rotorcraft Ditching.

A list of organizations represented on this committee can be obtained on request to its committee manager.

The International Maritime Organisation code for life-saving appliances requires a lifejacket to lift the mouth clear of the water and to self-right an unconscious person. This requirement should be fully applied to all aviation survival equipment configurations which will comprise a lifejacket and may include an emergency breathing system and/or an immersion suit.

Where the survival equipment includes an immersion suit, the inherent buoyancy of the immersion suit can impede self-righting. This may necessitate the use of a larger lifejacket or buoyancy element, which can then adversely affect other aspects of survival, such as life raft boarding. This self-righting issue may occur with larger immersion suit sizes and more heavily insulated suits, specifically immersion suits in Categories 3 or 4 (as set out in the new immersion suit standard BS EN 4863:2022 and discussed in this standard BS EN 4862:2022 and the new emergency breathing system standard BS EN 4856:2022).

In a review of aircraft Certification Specifications conducted by EASA (EASA Notice of Proposed Amendment NPA 2016-01), the absence of a clear requirement for self-righting of lifejacket and immersion suit combinations or integrated immersion suits was found to be anomalous, and was part of the motivation for the development of this Standard. A UK Civil Aviation Authority (CAA) review of offshore helicopter operations, following a fatal helicopter accident in August 2013 (Civil Aviation Publication CAP 1145), recommended that all lifejacket and immersion suit combinations used in service should be capable of self-righting.

In this British Standard (BS EN 4862:2022), self-righting is required for all configurations employing Category 1 and 2 suits. For Category 3 immersion suit configurations, at least two thirds of test subjects must self-right during testing. For Category 4 immersion suit configurations, none of the test subjects are required to self-right during testing.

Testing of a range of lifejacket and immersion suit combinations performed during the development of BS EN 4862:2022 and BS EN 4863:2022, by an accredited test house in the UK, indicated that self-righting when using Category 1, 2 or 3 immersion suits is achievable.

Given the prevailing water temperatures associated with operations on the UK Continental Shelf, it is unlikely that Category 4 immersion suits will be used. However, Category 3 immersion suits may be used and, as recommended by the UK CAA (CAP 1145), it is the UK committee's opinion that all occupants should be provided with a survival equipment configuration that will self-right.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be