

Passive filter units for electromagnetic interference suppression –

**Part 2: Sectional specification: Passive filter units for which safety tests are appropriate –
Test methods and general requirements**

CORRIGENDUM 1

Page 10

1.5.2

Replace the existing text by the following:

The filter shall be clearly marked with the information in 1.5.1 a), b), c), d) and f), and also e) if this is not implied by b).

Page 19

4.4.2 Applied voltage

Replace the first sentence by the following:

The voltages given in Table 9 shall be applied between the measuring points of Table 3 of IEC 60939-1 for a period of 1 min for qualification approval and periodic testing and for a period of 2 s for lot-by-lot quality conformance testing.

Page 21

4.7 Insertion loss

Replace the first phrase by the following:

See 4.7 of IEC 60939-1 with the following details:

Page 21

4.8 Discharge resistance

Replace the first sentence by the following:

See 4.8 of IEC 60939-1.

Page 22

4.9 Robustness of terminations

Replace the first phrase by the following:

See 4.9 of IEC 60939-1 with the following details:

Page 22

4.10 Resistance to soldering heat

Replace the second sentence by the following:

See 4.10 of IEC 60939-1 with the following details:

Page 22

4.11 Solderability

Replace the second sentence by the following:

See 4.11 of IEC 60939-1, with the following details:

Page 22

4.11.2 Requirements

Replace the first sentence by the following:

See 4.11.2, 4.11.3 and 4.11.4 of IEC 60939-1.

Page 22

4.12 Rapid change of temperature

Replace the first sentence by the following:

See 4.12 of IEC 60939-1 with the following details:

Page 23

4.13 Vibration

Replace the first sentence by the following:

See 4.13 of IEC 60939-1 with the following details:

Page 23

4.14 Bump

Replace the second sentence by the following:

See 4.14 of IEC 60939-1 with the following details: