

INTERNATIONAL ELECTROTECHNICAL COMMISSION

IEC TR 61282-14 Edition 1.0 2016-01

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

Part 14: Determination of the uncertainties of attenuation measurements in fibre plants

CORRIGENDUM 1

Replace the existing Table C.1 with the following new table:

Table C.1 – Spectral attenuation coefficients

	Domain nm	α_0	α_1	α_2	α_3	α_4	α_5	α_6
MM A1	800 to 1 350	$5,241\,88 \times 10^{-01}$	$2,937\,83 \times 10^{-03}$	$6,850\,36 \times 10^{-06}$	$8,485\,88 \times 10^{-09}$	$5,883\,55 \times 10^{-12}$	$-2,163\,8 \times 10^{-15}$	$3,297\,25 \times 10^{-19}$
SM B1.3	1 285 to 1 385	$-7,510\,8 \times 10^{-02}$	$1,719\,89 \times 10^{-04}$	$1,309\,54 \times 10^{-07}$	$3,318\,81 \times 10^{-11}$	0	0	0
SM B1.3	1 385 to 1 675	$1,375\,6 \times 10^{-01}$	$3,623\,94 \times 10^{-04}$	$3,586\,79 \times 10^{-07}$	$1,579\,87 \times 10^{-10}$	$2,612\,47 \times 10^{-14}$		