

INTERNATIONAL STANDARD

ISO/IEC
11518-3

First edition
1996-06-15

Information technology — High-Performance Parallel Interface —

Part 3:

Encapsulation of ISO/IEC 8802-2 (IEEE Std 802.2)
Logical Link Control Protocol Data Units (HIPPI-LE)

Technologies de l'information — Interface parallèle à haute performance —

*Partie 3: Encapsulation de l'ISO/CEI 8802-2 (IEEE Std 802.2) unités de
données du protocole de contrôle de liaison logique (HIPPI-LE)*



Reference number
ISO/IEC 11518-3:1996(E)

Contents

	Page
Foreword	ii
Introduction	iv
1 Scope.....	1
2 Normative references	1
3 Definitions and conventions.....	1
3.1 Definitions	1
3.2 Editorial conventions	1
4 HIPPI-LE services to ISO/IEC 8802-2 LLC	2
4.1 Service primitives types	2
4.2 Sequences of primitives.....	2
4.3 HIPPI-LE service primitive summary	2
4.4 HIPPI-LE transfer service primitives	3
4.5 HIPPI-LE address resolution primitives	4
4.6 HIPPI-LE station management service primitives	5
5 HIPPI-FP data framing services used by HIPPI-LE.....	6
6 HIPPI-LE data formats.....	6
6.1 HIPPI-LE PDU format	6
6.2 ISO/IEC 8802 48-bit address format.....	8
7 HIPPI Address Resolution	8
7.1 Overview	8
7.2 Address Resolution in Detail	8
Annexes	
A Example HIPPI packets containing HIPPI-LE PDUs	11
B Bibliography	15
Alphabetical index	16
Figures	
1 Protocol hierarchy	iv
2 HIPPI-LE service relationship	2
3 Data transfer service primitives	3
4 HIPPI-LE Address resolution service primitives	4
5 Station management service primitives	5
6 HIPPI-LE header format	7
7 Mapping of 6-byte ISO/IEC 8802-2 universal LAN MAC address to two 32-bit HIPPI words in LE_Header.....	7

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland