
**Information technology — Data interchange
on 356 mm optical disk cartridges —
WORM, using phase change technology —
Capacity: 14,8 Gbytes and 25 Gbytes per
cartridge**

*Technologies de l'information — Échange de données sur cartouches de
disques optiques 356 mm [WORM], utilisant la technologie de changement
de phase — Capacité: 14,8 Gbytes et 25 Gbytes par cartouche*

Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Optical disk cartridge	1
2.2 Generating system	1
2.3 Receiving system	1
2.4 Compatibility statement	1
3 Normative references	1
4 Definitions	2
4.1 actual write power	2
4.2 air sandwich disk	2
4.3 band	2
4.4 baseline reflectance	2
4.5 birefringence	2
4.6 case	
4.7 clamping zone	2
4.8 cover sheet	2
4.9 cross-talk level	2
4.10 cyclic redundancy check (CRC)	2
4.11 defect management	2
4.12 disk reference plane	2
4.13 entrance surface	2
4.14 error correction code (ECC)	2
4.15 error detection and correction (EDAC)	2
4.16 format	2
4.17 hub	2
4.18 interleaving	2
4.19 mark	2
4.20 mark edge	2
4.21 mark edge recording	2
4.22 narrow band signal-to-noise ratio	2
4.23 noise floor	2
4.24 optical disk	2
4.25 optical disk carrier	3
4.26 optical disk cartridge (ODC)	3
4.27 optical retardation	3
4.28 perimeter ring	3
4.29 pre-formatted mark	3

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland