

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 1799

DIMENSIONS OF ELASTOMERIC TOROIDAL SEALING RINGS
FOR PIPE-FITTINGS IN AIRCRAFT

(INCH SERIES – CLASS 2 TOLERANCES)

1st EDITION

January 1971

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

DIMENSIONS OF ELASTOMERIC TOROIDAL SEALING RINGS FOR PIPE-FITTINGS IN AIRCRAFT

(INCH SERIES — CLASS 2 TOLERANCES)

1. SCOPE

This ISO Recommendation states the dimensions and a method of designation for a range of elastomeric toroidal sealing rings in inch sizes with Class 2 tolerances, suitable for use with pipe-fittings screwed into tapped bosses conforming to the dimensions stated in an ISO Recommendation at present in preparation. It does not make reference to materials to be used for the rings. Rings with Class 1 tolerances are the subject of ISO Recommendation R 1077, *Dimensions of elastomeric toroidal sealing rings for pipe-fittings in aircraft (Inch series — Class 1 tolerances)*.

2. DIMENSIONS

The dimensions of toroidal sealing rings for use with pipe-fittings screwed into tapped bosses should comply with the Table opposite.

3. DESIGNATION

The sealing rings should be designated by the ring size numbers quoted in the Table opposite.